

smartTAP Water Dispenser

Water dispensing system for public water points

ORDER INFORMATION

- Item no.: 40-000000
- Product name: water dispenser 01-22-A with PV module, 3m cable and PV pole mounting bracket (NOTE - battery not included)
- Item no.: 19-001600
- Product name: dispenser tag, 50 pcs

FEATURES


- Secure NFC tag based water dispenser
- Intuitive user interface, high user acceptance, accessible for all irrespective of age, gender or capabilities
- Robust and secure housing
- 10 Wp solar module for charging
- Integrated battery charging for 24 hour use

TECHNICAL DATA

PV input Umax 24 V DC Max. pressure 3 bar Min. pressure 0.1 bar Flow at 0.2 bar 19 l/min Flow at 3 bar 54 l/min Accuracy > 95 % Battery NP7-12 lead acid Battery input U 12 V DC Bluetooth FCCID:QQQBT127 ** Optional integrated GSM modem: 2G / 3G communication R&TTE, GCF, CE, FCC, PTCRB, IC, UL and AT&T approvals External antenna

For public water points Toppod Introduction and Adjight Lorentz Lorentz Lorentz

HYDRAULIC PERFORMANCE



ENVIRONMENTAL DATA

For drinking water - max 40 °C

Enclosure IP66

Operating temp (ambient) 0 to 45 °C

non-freezing

Humidity max. 95 %

PRODUCT DIMENSION/WEIGHT

 Height
 400 mm / 15.75 "

 Length
 300 mm / 11.81 "

 Width
 187 mm / 7.36 "

 Weight (dispenser)
 4.8 kg

Weight (PV module, cable) 1.36 kg

PACKING DIMENSION/WEIGHT

 $\begin{array}{ccc} \text{Dimensions} & 500\,\text{mm}\times380\,\text{mm} \\ & \times 295\,\text{mm} \\ \text{Weight} & 6.5\,\text{kg} \end{array}$

BERNT LORENTZ GmbH

Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany Tel. +49 (0) 4193 8806 - 700, www.lorentz.de

